

Xerox® Phaser® 4622 Black and White Printer



	Phaser 4622DN		
Output Speed	Up to 62 ppm A4 / 210 x 297 mm		
Automatic Two-sided	Up to 43 ppm A4 / 210 x 297 mm		
Paper Handling – Input			
Multipurpose Tray – Tray	1		
Capacity ¹	100 sheets		
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm		
Weights	60 to 220 gsm		
Media Types	Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Envelopes Letterhead Hole punched Archive Transparencies Recycled Bond		
Tray 2			
Capacity ¹	550 sheets		
Sizes	Custom sizes: 98.6 x 148.5 mm to 216 x 356 mm		
Weights	60 to 163 gsm		
Media Types	Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Letterhead Hole punched Archive Recycled Bond		
Up to 4 Additional Trays (Optional) – Only 2 additional trays can be used if the optional High Capacity Feeder is installed		
Capacity ¹	550 sheets each		
Sizes	Custom sizes: 139.7 x 210 mm to 216 x 356 mm		
Weights	60 to 163 gsm		

Mediα Types	Plain Plain thick Other Card stock Lightweight Heavyweight Rough surface Labels Letterhead Hole punched Archive Recycled Bond
High Capacity Feeder – You	ı cannot add a High Capacity Feeder if more than 4 paper trays are being utilised.
Capacity	2,000 sheets
Sizes	A4
Weights	60 to 90 gsm
Media Types	Plain Punched Pre-printed Recycled Bond Archive Letterhead Custom
Paper Input Capacity	
Standard Paper Capacity ¹	650 sheets
Maximum Paper Capacity ¹	3,750 sheets
Paper Output	
Automatic Two-sided Output	500 sheets
Print	
First-page-out Time	As fast as 7.8 seconds
Print Resolution	Up to 1200 x 1200 dpi
Maximum Print Area	4 mm from all edges or 207.7 mm x 347.4 mm (default)
Memory (std / max)	256 MB / 768 MB optional 320 GB HDD
Processor	600 MHz Dual-core ARM
Page Description Languages	PCL® 5e and 6 emulations PostScript® 3™ emulation PDF emulation Epson
Connectivity	10/100/1000Base-T Ethernet, High Speed USB 2.0, Optional Wireless 802.11n with WPA 2 Enterprise
Print Features	Booklet printing Scaling Fit to page Watermarks Custom-size pages N-up Secure print Collation Personal print Smart duplex
Supported Operating Systems	Microsoft® Windows® XP SP1, Vista, 7, Windows 8, Windows 8.1, 2008 Server, 2003 Server, 2012 Server Mac OS® 10.5 and later Various Linux® and UNIX® distributions, including: • IBM® AIX® 5 • HP-UX® 11i v2 • openSUSE® 11 • Red Hat® Fedora® Core 11-14 • Ubuntu®

Print Queue Viewing

Print Drivers	Microsoft Windows XP and above 2003 Server and above Mac OS 10.5 and above Red Hat Enterprise 4, 5 Fedora Core 14-16 openSUSE 11, 12 IBM AIX-5 HP-UX 11, 11i Solaris® 9, 10 Ubuntu Xerox® Global Print Driver® Xerox® Mobile Express Driver®			
Font Capability	136 PostScript® Fonts; 93 PCL® Fonts			
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management			
Security				
Security Features	Secure HTTPS (SSL) IPsec 802.1X Authentication Network Authentication IPv6 SNMPv3 Image Overwrite Audit Log Xerox Secure Access Unified ID System® (optional) IP Filtering Secure Print			
Wi-Fi Security				
	Authentication Method	Encryption	Productivity Kit	
	Open WPA PSK WPA PSK / WPA2 PSK	WEP 64 / 128 ASCII / HEX TKIP AES	No	
	WPA Enterprise WPA Enterprise / WPA 2™ Enterprise WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP	TKIP AES	Yes	
Device Management				
Xerox [®] CentreWare [®] Web	 A Web-based server application for network administra from any workstation, whether running Windows or UN Works with any SNMP-managed printer from any man Provides help with device discovery and installations, he as well as basic accounting and asset management 	NIX or any other operating sys ufacturer	tem	
Xerox® CentreWare® Intern	et Services – Integrated Device Web Page			
Device Status	Web server embedded • Tray status / contents • Consumables status			
Drint Ougus Viewing				

Complete job print queue management – hold, release, promote and delete

Job Submission	Print-ready files (PS, PCL ^o Output feature selection				
Device Administration	Allows simple, remote in:	stallation setting of con	figuration options and manag	gement of the device	
Browsers	Microsoft® Internet Explorer® 7 Firefox® version 4 and above				
Xerox® Mobile Solutions	'				
Xerox® PrintBack	PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple® iOS- or Android™-based mobile device. When you're working off-site or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF etc.) with uncompromised print quality.				
Xerox [®] Mobile Express Driver [®]	The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver.				
Apple® AirPrint	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.				
Device Specifications					
Duty Cycle					
	Up to 275,000 pages per month ²				
Recommended Monthly Pri	int Volume				
	Up to 25,000 pages per	month ³			
Power Consumption					
220 to 240 VAC 50 / 60 Hz	, 5.0 A				
Continuous Printing	4622V_ADN (52 ppm): 820 watts; 4622V_DN (62 ppm): 900 watts				
Ready (Standby) Mode	4622V_ADN (52 ppm): 110 watts; 4622V_DN (62 ppm): 120 watts				
Energy Saver Mode (Sleep)	4622V_ADN (52 ppm) a	nd 4622V_DN (62 ppm): 2.8 watts		
Environment					
Warm-up Time (from Power Save)	First print: As fast as 45 seconds User Interface ready and programmable: 2 seconds				
Warm-up (from Power On)	65 seconds User Interface ready and programmable: 54 seconds (max)				
Temperature Range	10°-32° C				
Humidity	20-85 %				
Sound Pressure Levels					
Printing / Copying	58 dB(A)				
Standby	30 dB(A)				
Quiet Mode Printing	52 dB(A)				
Energy Save Mode	0 dB(A)				
Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight	
Phaser 4622	476 mm	541 mm	420 mm	34.6 kg	
550-sheet Feeder	464 mm	521 mm	148 mm	13.2 kg	
High Capacity Feeder	480 mm	569 mm	451 mm	33 kg	
Finisher	410 mm	444 mm	424 mm	7.9 kg	
Mail Box	351 mm	296 mm	422 mm	3.6 kg	
Stand	480 mm	553 mm	84 mm	17.1 kg	

Dimensions and Weights (1		1	1	
Phaser 4622	627 mm	698 mm	685 mm	40.2 kg	
550-sheet Feeder	656 mm	715 mm	334 mm	13.2 kg	
High Capacity Feeder	670 mm	840 mm	587 mm	33 kg	
Finisher	595 mm	484 mm	453 mm	11.1 kg	
Mail Box	461 mm	366 mm	457 mm	6.3 kg	
Stand	682 mm	609 mm	290 mm	17.1 kg	
Certifications					
	Listed to UL 60950-1/CSA 60950-1-07+A1:2011, 2nd Edition, FDA/CDRH – Class 1 Laser Product, FCC Part 15, Class A, Canada ICES-003, Class A, CE marked, Low Voltage Directive 2006/95/EC, EN 60950-1, 2nd Edition, EN 60825-1 – Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class A, EN 55024, RoHS Directive 2011/65/EC, WEEE Directive 2002/96/EC, ENERGY STAR qualified, Section 508 Compliant, Blue Angel certified TAA compliant (requires YDN configuration)				
	To view the latest list of cert	cifications, go to www.xerox.	com/OfficeCertifications.		
What Comes in the Box					
	Phaser 4622 Printer Toner cartridge (13,000 page capacity ⁵) Drum cartridge Quick Installation Guide, Quick Use Guide, Driver CD, Documentation CD (User Manual, System Admin. Guide Power cable				
Supplies and Options	Description			Order Number	
Standard Capacity Toner Cartridge	13,000 impressions ⁵			106R01533	
High Capacity Toner Cartridge	30,000 impressions ⁵			106R01535	
TTA compliant High Capacity Toner Cartridge	30,000 impressions ⁵			106R02638	
Xerox® SmartKit® Drum Cartridge	80,000 impressions ⁶			113R00762	
TAA compliant Drum Cartridge	80,000 impressions ⁶			113R00769	
Options				Order Number	
Hard Drive Kit: 320 GB	097N02157				
550-sheet Paper Tray				097N01874	
2,000-sheet High Capacity Feeder (includes stand)			097N01875		
2,000-sheet High Capacity	reeder (includes stand)				
2,000-sheet High Capacity Finisher / Stapler	reeder (mciddes stand)			097N01876	
	reeder (includes stand)			097N01876 097N01877	

 $^{^{\}rm 1}$ Paper capacities are based on 75 gsm stock. Capacities will vary with different weight stocks.

512 MB Memory

Internal Wireless Network Adapter



097N01878

097N01880

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

⁴ Phaser 4622V_ADN is the Blue Angel compliant configuration at 52 ppm.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared Yield based on A4 (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.